



DOTAZIONI - SUPPLIED WITH - AUSSTATTUNG

N*1 Boccola di riduz. $\varnothing 16-\varnothing 12$ e N*1 Boccola di riduz. $\varnothing 16-\varnothing 10$
 N*1 Reduction bush $\varnothing 16-\varnothing 12$ and N*1 Reduction bush $\varnothing 16-\varnothing 10$
 N*1 Reduzierbuchsen $\varnothing 16-\varnothing 12$ und N*1 Reduzierbuchsen $\varnothing 16-\varnothing 10$

PER UTENSILI STOZZATORI VEDI PAG. TBL400-1-00
 FOR DRIVEN SLOTTING TOOL CUTTING-TOOLS SEE PAGE TBL400-1-00
 FÜR NUTENSTOSS-WERKZEUG SCHNEIDWERKZEUGE SIEHE SEITE TBL400-1-00

Cod. MT	I	RPM MAX	Reversibile lato mandrino/contromandrino Reversible sub/main spindle side Umkehrbare Spindel-seite/ Gegenspindel-seite	Lubr. esterna Ext. coolant Aussenkuehlung
DW01980100	4:1	2000	X	X

SMART

MOD: NL4000/5000 M/LM/LY

MODULO MOTORIZZATO STOZZATORE CORSA 50mm H=90mm

Slotting driven tool 50mm stroke H=90mm

Keilnutenstossmaschine 50mm Hub H=90mm

Subject to change without notice.

M.T. srl

Via Casino Albini 480
 Tel. 0541/956034-957884
 Fax 0541/956341
 47842 S. GIOVANNI IN M. (RN)
 e-mail: mtma@tmarchetti.com
 http://www.tmmarchetti.com



SMA360-3-00

09/2024