



DOTAZIONI - SUPPLIED WITH - AUSSTATTUNG

N°1 Boccola di riduz. $\varnothing 16$ - $\varnothing 12$ e N°1 Boccola di riduz. $\varnothing 16$ - $\varnothing 10$
 N°1 Reduction bush $\varnothing 16$ - $\varnothing 12$ and N°1 Reduction bush $\varnothing 16$ - $\varnothing 10$
 N°1 Reduzierbuchsen $\varnothing 16$ - $\varnothing 12$ und N°1 Reduzierbuchsen $\varnothing 16$ - $\varnothing 10$

PER UTENSILI STOZZATORI VEDI PAG. TBL400-1-00
 FOR DRIVEN SLOTTING TOOL CUTTING-TOOLS SEE PAGE TBL400-1-00
 FÜR NUTENSTOSS-WERKZEUG SCHNEIDWERKZEUGE SIEHE SEITE TBL400-1-00

Cod. MT	I	RPM MAX	Reversibile lato mandrino/contromandrino Reversible sub/main spindle side Umkehrbare Spindel-seite/ Gegenspindel-seite	Lubr. esterna Ext. coolant Aussenkuehlung
TSM0210200	4:1	2400	X	X

TSUGAMI

MOD: M06 - M08

MODULO MOTORIZZATO STOZZATORE CORSA 25mm H=90mm

Slotting driven tool 25mm stroke H=90mm

Keilnutenstossmaschine 25mm Hub H=90mm

Subject to change without notice.

M.T. srl

Via Casino Albini 480
 Tel. 0541/956034-957884
 Fax 0541/956341

47842 S. GIOVANNI IN M. (RN)
 e-mail: mtma@mtmarchetti.com
 http://www.mtmarchetti.com



TSM360-3-01

09/2024